

V O L V O



Volvo Wheel Loaders 24.1-33.1 t / 53,130-72,970 lb 295-367 hp

L150H, L180H, L220H

Volvo Construction Equipment



Smarter, stronger, faster

The new H-series L150, L180 and L220 may boast the same striking design as each of its forerunners, but these machines have been updated with the latest innovative technology, promoting greater productivity and fuel efficiency. Ready to tackle a range of applications, enjoy the same reliability and quality you'd expect from your Volvo wheel loader and more.

1954

The world's first wheel loader to feature a parallel lift arm system and attachment bracket with quick coupler – the H-10

1973

The first wheel loader with direct injected turbo engine – Volvo BM 1641

Volvo introduced the world's first truly low-emission diesel engines in construction equipment (1974)

1981

Volvo introduced the world's first automatic gear shifting system (Automatic Power Shift) and load sensing hydraulic technology

1988

Comfort Drive Control




Progress is in our DNA

Since introducing our first wheel loader, Volvo has continued to refine its concept for more than half a century. Over the years, we have revolutionized our machines, bringing customers unparalleled productivity and efficiency.

With you for the long run

As your trusted partner in production, Volvo is here to support you with the best equipment for the job. Boasting a comprehensive portfolio of attachments designed to complement your machines performance, as well as a range of services to boost your profitability, we'll help you tailor the perfect package to suit your business needs.



Smarter operation

Primed for productivity, the innovative L150H, L180H and L220H loaders combine the latest Volvo technology, including second generation OptiShift, with power and upgraded features, resulting in up to 15% better fuel efficiency than the G-series.


Up to 15% greater fuel efficiency

Do more with less fuel, the H-series machine updates offer up to 15% greater fuel efficiency than the G-series. Contributing to the increase is the powerful engine, second generation OptiShift, attachment optimization and the new dry P-Brake, which eliminates drag losses.




Reverse By Braking

Extend the life of your machine's components and increase operator comfort with Reverse By Braking (RBB) – patented by Volvo. The braking function slows the machine when the operator wants to change direction, by reducing engine rpm and automatically applying the service brakes, reducing stress on the drivetrain.



Power up, fuel down

For short cycle times and high fuel efficiency, the H-series wheel loaders are fitted with a powerful Volvo engine – compliant with the latest emission regulations – delivering greater output and torque than the G-series.



Eco pedal

Save on machine wear and increase fuel efficiency with the eco pedal. Uniquely designed by Volvo, the eco pedal encourages economical operation, by applying a mechanical push-back force in response to excess use of the accelerator.





NEW GENERATION OPTISHIFT

For improved cycle times and reduced fuel consumption, customize the lock-up engagement of your machine, with new generation OptiShift. The improved technology integrates the Reverse By Braking function and the new torque converter with lock-up, creating a direct drive between the engine and transmission.

Made to move

Engineered for efficient work, the L150H, L180H and L220H are fitted with a new transmission and improved technology, resulting in up to 10% better productivity than the G-series.

Boost your productivity by up to 10%

For ultimate stability and high efficiency, the H-series wheel loaders have been upgraded with a new transmission, which works in harmony with the engine and axels. The new converter delivers increased torque output, resulting in better performance at low speeds. For faster acceleration and smooth operation, the steps between gears have been reduced.



Fast cycle times

Achieve shorter cycle times with next generation load sensing hydraulics, designed to enhance the responsiveness of attachments and improve the lifting and lowering speed of the boom.



Comfortably productive

Customize your machine and ensure precise control of hydraulic functions, with the choice of single or multi levers. To get the most out of each operation, select from three hydraulic modes, according to your preferred responsiveness.



Bucket leveling function

Take your productivity to the next level with the new bucket leveling function. Automatically return the bucket to level from both dump and curl positions, enhancing operator performance.



Load Assist

Optimize your load cycles with Load Assist, powered by Volvo Co-Pilot – the 10” in-cab display. Gain access to a set of smart apps and boost the efficiency of your operation. The rear-view camera and optional radar detect system are now integrated into the Volvo Co-Pilot.

On-Board Weighing

Make overloading, underloading, reweighing and waiting times a thing of the past with On-Board Weighing, providing real-time insight into the bucket's load. What's more, with the new Simple Mode, it has never been easier to start reaping the benefits of On-Board Weighing.



Operator Coaching

Operator Coaching helps to ensure operators are using their Volvo machine to its full potential. The intuitive app provides real-time guidance to operators, helping them understand how their actions influence machine productivity and efficiency, as well as identify areas for improvement or changes in their technique.



Tire Pressure Monitoring System

With the tire pressure monitoring app, you can check the condition of your tires from the comfort of the cab. Providing real-time information on tire pressure and temperature, the system saves time during machine inspections and can prolong tire lifetime.



Map

Get accurate machine positioning with Map, a clever app that allows operators to monitor on-site traffic in real-time. Not only does this give operators an improved orientation of the site they are working on, but it allows them to proactively adjust their driving behavior according to traffic conditions.



Fully loaded

Get the most out of your Volvo wheel loader with a range of purpose built attachments. Form one solid and reliable unit, with attachments that are ideally matched by size and design to your machine's parameters – including link-arm geometry, breakout and lifting forces. If we don't have the right attachment, Volvo can custom build one to your specific requirements.


Rehandling

Experience up to 5% greater productivity with a new range of Volvo Rehandling buckets. The redesigned buckets are easier to fill and minimize spillage, thanks to new convex sides and the improved spill guard. To prevent spillage and absorb shocks, opt for the Boom Suspension System, which automatically engages, depending on gear or speed selection.



Block handling

For high lifting force and maximum stability in block handling applications, choose from a range of robust Volvo attachments, including block forks, breaker tine and clearing rakes.



Slag handling

To protect you and your machine, and ensure durable performance in hot slag handling applications, Volvo offers a selection of specially-designed machine options and attachments.



Log handling

Designed for high lifting force and tilt out force, and offering maximum stability in log handling applications, select from a choice of general purpose grapples, sorting grapples and unloading grapples.





TORQUE PARALLEL LINKAGE

For strength in demanding applications, Volvo's unique Torque Parallel (TP) linkage provides high breakout torque and ultimate parallel movement throughout the entire lifting range. The linkage offers stability during loading and carrying and allows easy filling of the buckets. For long lasting performance, the lifting arm has double sealing on each of the pins.

Strong and smart machines

Built with the operator in mind

- Adjustable seat
- Choice of three hydraulic modes
- Comfort Drive Control (option)
- Radar detect system (option)
- Remote-control door opener (option)
- Collision Mitigation System (option)

Up to 15% greater fuel efficiency

- Rimpull control
- New generation OptiShift
- Reverse By Braking
- Eco pedal
- Dry P-brake



Boost your productivity by up to 10%

- New load sensing hydraulics
- New transmission and gear ratio
- Bucket leveling function
- Load Assist, powered by Volvo Co-Pilot
- Choice of single or multi levers

Maximize your uptime

- Lifetime Frame and Structure Warranty
- 1000hr engine oil change interval
- Quicker hydraulic oil fill thanks to new mounted nipple
- Tilting cab, electronically-operated engine hood
- Brake wear indicators
- Outboard mounted brakes
- Replaceable breather filters

Fully loaded

- Unique Torque Parallel linkage
- Block handling
- Slag handling
- Log handling
- Rehandling – up to 5% greater productivity

Here to support you

- Genuine Volvo Parts
- Operator training
- ActiveCare Direct



Built with the operator in mind

Built with the customer, for the customer, the L150H, L180H and L220H boast a range of features to enhance your operating experience. For increased productivity, the Volvo cab can be customized to your preference.

Visibility

To enhance visibility, the H-series wheel loaders can be equipped with a rear-view camera. Optimized by the radar detect system, which works with the camera to give a visual and audible alert to the operator of unseen on-coming objects. Orange handrails and steps have been placed on the machine, intended to stand out to the operators and maintenance staff.



Comfort Drive Control

To reduce operator fatigue and improve productivity, Comfort Drive Control can be optionally integrated into your machine. The smart function gives you the opportunity to steer the machine from a small lever – particularly effective for fast-paced truck loading operations.



Operator training

Increase productivity and reduce fuel consumption by learning how to operate your wheel loader in the most efficient way. Volvo offers operator training, which encompasses the best practices in the industry.



Collision Mitigation System

The Collision Mitigation System has been developed to support the safe operation of Volvo Wheel Loaders. The optional system assists operators while working in reverse by automatically applying the brakes when the machine approaches an obstacle, helping to reduce the risk or consequences of collisions and enhance jobsite safety.





THE OPERATOR'S CHOICE

Operate in comfort from the best cab on the market, the Volvo cab can be equipped with a new adjustable seat. Access the cab safely and effortlessly using the steps and open the door with ease, thanks to the optional remote-control opener.

Keep moving

Offering strength in demanding applications, the L150H, L180H and L220H are built to last. Maintain the life of your machine with simple serviceability and proactive dealer support.

Durable by design

Designed with durability in mind, the H-series wheel loaders are built with a Lifetime Frame and Structure Warranty, including the front frame, rear frame, articulation joint and loader arm. The hydraulically-driven cooling fan regulates component temperature and can be automatically reversed to permit self-cleaning of the cooling units. For long service life, the brakes are outboard mounted and the front and rear axles are cooled by the oil circulation.



ActiveCare Direct

Keep your machine moving with ActiveCare Direct. Volvo monitors machine health remotely, from our very own Uptime Center, helping to predict potential failures before they occur. This gives you more time to focus on your operation, helping to reduce unplanned downtime and minimize repair costs.



Here to support you

Maintain productivity and machine uptime with our range of Genuine Volvo Parts – all backed by Volvo warranty, with 24-hour parts delivery guarantee. We're here to help you stay on track, offering flexible maintenance and repair plans.





INDUSTRY LEADING SERVICEABILITY

For simple servicability, the Volvo cab can be tilted to either a 30° or 70° angle, and the engine hood is operated electronically. Stay one step ahead and check the condition of your brakes using the brake wear indicators, placed on the wheels. To prevent dirt and moisture from entering components, each has replaceable breather filters, located remotely.

Volvo L150H, L180H, L220H in detail


Engine

V-ACT Stage IV/Tier 4F 13 liter, 6-cylinder straight turbocharged diesel engine with 4 valves per cylinder, overhead camshaft and electronically controlled unit injectors. The engine has wet replaceable cylinder liners and replaceable valve guides and valve seats. The throttle applications is transmitted electrically from the throttle pedal or the optional hand throttle. Air Cleaning: 2 stages. Cooling system: Hydrostatic, electronically controlled fan and intercooler of the air-to-air type.

L150H

Engine	Volvo	D13J
Max. power at	r/min (r/s)	1,300 (21.7)
SAE J1995 gross	kW (hp)	220 (295)
ISO 9249, SAE J1349 net	kW (hp)	220 (295)
Max. torque at	r/min (r/s)	1,000 (16.7)
SAE J1995 gross	Nm (ft lbf)	1,960 (1,446)
ISO 9249, SAE J1349 net	Nm (ft lbf)	1,957 (1,443)
Economic working range	r/min (r/s)	800 - 1,600 (13.3 - 26.7)
Displacement	l (in ³)	12.8 (781)


L150H



L180H

Engine	Volvo	D13J
Max. power at	r/min (r/s)	1,300 - 1,400 (21.7 - 23.3)
SAE J1995 gross	kW (hp)	246 (330)
ISO 9249, SAE J1349 net	kW (hp)	245 (329)
Max. torque at	r/min (r/s)	1,000 (16.7)
SAE J1995 gross	Nm (ft lbf)	2,030 (1,497)
ISO 9249, SAE J1349 net	Nm (ft lbf)	2,024 (1,493)
Economic working range	r/min (r/s)	800 - 1,600 (13.3 - 26.7)
Displacement	l (in ³)	12.8 (781)


L180H



L220H

Engine	Volvo	D13J
Max. power at	r/min (r/s)	1,300 - 1,400 (21.7 - 23.3)
SAE J1995 gross	kW (hp)	274 (367)
ISO 9249, SAE J1349 net	kW (hp)	273 (366)
Max. torque at	r/min (r/s)	1,100 (18.3)
SAE J1995 gross	Nm (ft lbf)	2,231 (1,645)
ISO 9249, SAE J1349 net	Nm (ft lbf)	2,220 (1,637)
Economic working range	r/min (r/s)	800 - 1,600 (13.3 - 26.7)
Displacement	l (in ³)	12.8 (781)

L220H



Drivetrain				
Torque converter: Single-stage. Transmission: Volvo countershaft transmission with single lever control. Fast and smooth shifting of gears with Pulse Width Modulation (PWM) valve. Torque converter with lockup. Transmission: Volvo Automatic Power Shift (APS) with fully automatic shifting 1-4 and mode selector with 4 different gear shifting programs, including AUTO. Also equipped with Rimpull control to avoid wheel spin and optimize bucket filling. Axles: Volvo fully floating drive shafts with planetary hub reductions and nodular iron axle housing. Fixed front axle and oscillating rear axle. 100% differential lock on the front axle. Optional: Limslip rear.				
		L150H	L180H	L220H
Transmission	Volvo	HTL 223	HTL 223	HTL 310
Torque multiplication, stall ratio		2.09:1	2.09:1	2.02:1
Maximum speed, forward/reverse				
1st gear	km/h (mi/h)	6.1 (3.8)	6.1 (3.8)	6.7 / 6.6 (4.2 / 4.1)
2nd gear	km/h (mi/h)	12.6 (7.8)	12.6 (7.8)	11.6 / 11.4 (7.2 / 7.1)
3rd gear	km/h (mi/h)	23.5 (14.6)	23.5 (14.6)	21.7 / 21.4 (13.5 / 13.3)
4th gear	km/h (mi/h)	38 (23.6)	38 (23.6)	36.5 / 36.1 (22.7 / 22.4)
Measured with tires		26.5 R25 L3	26.5 R25 L3	29.5 R25 L4
Front axle/rear axle		Volvo/AWB 40B/40C	Volvo/AWB 40B/40B	Volvo/AWB 50/41
Rear axle oscillation	± °	15	15	15
Ground clearance	mm (in)	610 (24)	610 (24)	600 (23.6)
at oscillation	°	15	15	15
Electrical system				
Central warning system: Contronic electrical system with central warning light and buzzer for following functions: - Serious engine fault - Low steering system pressure - Over speed warning engine - Interruption in communication (computer fault) Central warning light and buzzer with the gear engaged for the following functions. - Low engine oil pressure - High engine oil temperature - High charge air temperature - Low coolant level - High coolant temperature - High crank case pressure - Low transmission oil pressure - High transmission oil temperature - Low brake pressure - Engaged parking brake - Fault on brake charging - Low hydraulic oil level - High hydraulic oil temperature - Overspeeding in engaged gear - High brake cooling oil temperature front and rear axles.				
		L150H	L180H	L220H
Voltage	V	24	24	24
Batteries	V	2 x 12	2 x 12	2 x 12
Battery capacity	Ah	2 x 170	2 x 170	2 x 170
Cold cranking capacity, approx	A	1,000	1,000	1,000
Alternator rating	W/A	2,280/80	2,280/80	2,280/80
Starter motor output	kW	7	7	7

Brake System				
Service brake: Volvo dual-circuit system with nitrogen charged accumulators. Outboard mounted hydraulically operated, fully sealed oil circulation-cooled wet disc brakes. The operator can select automatic disengagement of the transmission when braking using Contronic. Parking brake: Dry disc brake. Applied by spring force, electro-hydraulic release with a switch on the instrument panel. Secondary brake: Dual brake circuits with rechargeable accumulators. One circuit or the parking brake fulfills all safety requirements. Standard: The brake system complies with the requirements of ISO 3450.				
		L150H	L180H	L220H
Number of brake discs per wheel front/rear		1/1	1/1	2/1
Accumulators	l (gal)	2 x 1.0 + 3 x 0.5 (2 x 0.26 + 3 x 0.13)	2 x 1.0 + 1 x 0.5 (2 x 0.26 + 1 x 0.13)	2 x 1.0 + 1 x 0.5 (2 x 0.26 + 1 x 0.13)
Cab				
Instrumentation: All important information is centrally located in the operator's field of vision. Display for Contronic monitoring system. Heater and defroster: Heater coil with filtered fresh air and fan with auto and 11 speeds. Defroster vents for all window areas. Operator's seat: Operator's seat with adjustable suspension and retractable seatbelt. The seat is mounted on a bracket on the rear cab wall and floor. The forces from the retractable seatbelt are absorbed by the seat rails. Standard: The cab is tested and approved according to ROPS (ISO 3471), FOPS (ISO 3449). The cab meets with requirements according to ISO 6055 (Operator overhead protection - Industrial trucks) and SAE J386 ("Operator Restraint System"). Refrigerant of the type R134a is used when this machine is equipped with air conditioning. Contains fluorinated greenhouse gas R134a, Global Warming Potential 1.430 t CO2-eq				
		L150H	L180H	L220H
Emergency exit: Use emergency hammer to break window				
Ventilation	m ³ /min (yd ³ /min)	9 (11.8)	9 (11.8)	9 (11.8)
Heating capacity	kW	16	16	16
Air conditioning (optional)	kW	7.5	7.5	7.5
Lift Arm System				
Torque Parallel linkage (TP-linkage) with high breakout torque and parallel action throughout the entire lifting range.				
		L150H	L180H	L220H
Lift cylinders		2	2	2
Cylinder bore	mm (in)	160 (6.3)	180 (7.1)	190 (7.5)
Piston rod diameter	mm (in)	90 (3.5)	90 (3.5)	90 (3.5)
Stroke	mm (in)	784 (30.9)	788 (31)	768 (30.2)
Tilt cylinder		1	1	1
Cylinder bore	mm (in)	220 (8.7)	240 (9.4)	250 (9.8)
Piston rod diameter	mm (in)	110 (4.3)	120 (4.7)	120 (4.7)
Stroke	mm (in)	452 (17.8)	480 (18.9)	455 (17.9)

Volvo L150H, L180H, L220H in detail

Hydraulic system

System supply: Two load-sensing axial piston pumps with variable displacement. The steering function always has priority.
Valves: Double-acting 2-spool valve. The main valve is electro operated.
Lift function: The valve has four positions; raise, hold, lower and floating position. Inductive/magnetic automatic boom kickout can be switched on and off and is adjustable to any position between maximum reach and full lifting height.
Tilt function: The valve has three functions including rollback, hold and dump. Inductive/magnetic automatic tilt can be adjusted to the desired bucket angle.
Cylinders: Double-acting cylinders for all functions.
Filter: Full flow filtration through 10 micron (absolute) filter cartridge.

		L150H	L180H	L220H
Working pressure maximum, pump 1 for working hydraulic system	MPa (bar)	29 (290)	29 (290)	29 (290)
Flow	l/min (gal/min)	180 (47.6)	217 (57.3)	252 (66.6)
at	MPa (bar)	10 (100)	10 (100)	10 (100)
engine speed	r/min (r/s)	1,900 (31.7)	1,900 (31.7)	1,900 (31.7)
Working pressure maximum, pump 2 for steering-, brake-, pilot- and working hydraulic system	MPa (bar)	31 (310)	31 (310)	31 (310)
Flow	l/min (gal/min)	202 (53.4)	202 (53.4)	202 (53.4)
at	MPa (bar)	10 (100)	10 (100)	10 (100)
engine speed	r/min (r/s)	1,900 (31.7)	1,900 (31.7)	1,900 (31.7)
Working pressure maximum, pump 3 for brake- and cooling fan system	MPa (bar)	25 (250)	25 (250)	25 (250)
Flow	l/min (gal/min)	83 (21.9)	83 (21.9)	83 (21.9)
at	MPa (bar)	10 (100)	10 (100)	10 (100)
engine speed	r/min (r/s)	1,900 (31.7)	1,900 (31.7)	1,900 (31.7)
Pilot system, working pressure	MPa (bar)	3.5 (35)	3.5 (35)	3.5 (35)
Cycle times				
Lift	s	5.9	6.4	6.8
Tilt	s	2	1.8	1.6
Lower, empty	s	3.7	3.3	3.2
Total cycle time	s	11.6	11.5	11.6

Steering System

Steering system: Load-sensing hydrostatic articulated steering.
System supply: The steering system has priority feed from a load-sensing axial piston pump with variable displacement.
Steering cylinders: Two double-acting cylinders.

		L150H	L180H	L220H
Steering cylinders		2	2	2
Cylinder bore	mm (in)	100 (3.9)	100 (3.9)	100 (3.9)
Rod diameter	mm (in)	60 (2.4)	60 (2.4)	60 (2.4)
Stroke	mm (in)	390 (15.4)	525 (20.7)	525 (20.7)
Working pressure	MPa (bar)	21 (210)	21 (210)	21 (210)
Maximum flow	l/min (gal/min)	202 (53.4)	202 (53.4)	202 (53.4)
Maximum articulation	± °	37	37	37

Service Refill

Service accessibility: Large, easy-to-open hood covering whole engine department, electrically operated. Fluid filters and component breather air filters promote long service intervals. A quick-fit adapter on the hydraulic tank provides faster hydraulic oil fill. Possibility to monitor, log and analyze data to facilitate troubleshooting.

		L150H	L180H	L220H
Fuel tank	l (gal)	366 (96.7)	366 (96.7)	366 (96.7)
DEF/AdBlue® tank	l (gal)	31 (8.2)	31 (8.2)	31 (8.2)
Engine coolant	l (gal)	55 (14.5)	55 (14.5)	55 (14.5)
Hydraulic oil tank	l (gal)	156 (41.2)	156 (41.2)	226 (59.7)
Transmission oil	l (gal)	48 (12.7)	48 (12.7)	48 (12.7)
Engine oil	l (gal)	50 (13.2)	50 (13.2)	50 (13.2)
Axle oil front	l (gal)	46 (12.2)	46 (12.2)	77 (20.3)
Axle oil rear	l (gal)	55 (14.5)	55 (14.5)	71 (18.8)

Sound Level

		L150H	L180H	L220H
Sound pressure level in cab according to ISO 6396				
L _{pA}	dB	69	70	70
External sound level according to ISO 6395 and EU Noise Directive 2000/14/EC				
L _{WA}	dB	108	108	109

Specifications

Tires L150H, L180H: 26.5 R25 L3. Tires L220H: 29.5 R25 L4



			Standard boom						Long boom					
			L150H		L180H		L220H		L150H		L180H		L220H	
B	mm	ft in	7,070	23'3"	7,190	23'7"	7,480	24'6"	7,570	24'10"	7,620	25'0"	7,800	25'7"
C	mm	ft in	3,550	11'8"	3,550	11'8"	3,700	12'2"	3,550	11'8"	3,550	11'8"	3,700	12'2"
D	mm	ft in	480	1'7"	480	1'7"	530	1'9"	470	1'7"	490	1'7"	530	1'9"
F	mm	ft in	3,580	11'9"	3,580	11'9"	3,730	12'3"	3,570	11'9"	3,590	11'9"	3,730	12'3"
G	mm	ft in	2,134	7'0"	2,134	7'0"	2,135	7'0"	2,157	7'1"	2,133	7'0"	2,133	7'0"
J	mm	ft in	3,920	12'10"	4,060	13'4"	4,230	13'11"	4,490	14'9"	4,560	14'11"	4,600	15'1"
K	mm	ft in	4,340	14'3"	4,470	14'8"	4,660	15'3"	4,900	16'1"	4,970	16'4"	5,020	16'6"
O	°		58		57		56		59		55		56	
P _{max}	°		50		49		48		49		49		48	
R	°		45		45		43		48		48		44	
R ₁ *	°		48		48		47		53		53		49	
S	°		66		71		65		61		63		63	
T	mm	ft in	93	0'3.7"	131	0'5.1"	119	0'4.7"	149	0'5.9"	207	0'8.2"	121	0'4.8"
U	mm	ft in	520	1'9"	570	1'10"	600	2'0"	640	2'1"	660	2'2"	680	2'3"
X	mm	ft in	2,280	7'6"	2,280	7'6"	2,400	7'10"	2,280	7'6"	2,280	7'6"	2,400	7'10"
Y	mm	ft in	2,960	9'9"	2,960	9'9"	3,150	10'4"	2,960	9'9"	2,960	9'9"	3,150	10'4"
Z	mm	ft in	3,510	11'6"	3,810	12'6"	4,050	13'3"	3,960	13'0"	4,180	13'8"	4,380	14'5"
a ₂	mm	ft in	6,790	22'3"	6,790	22'3"	7,100	23'4"	6,790	22'3"	6,790	22'3"	7,100	23'4"
a ₃	mm	ft in	3,820	12'7"	3,820	12'7"	3,960	13'0"	3,820	12'7"	3,820	12'7"	3,960	13'0"
a ₄	±°		37		37		37		37		37		37	

* Carry position SAE

Bucket: L150H: 4.0 m³ (5.2 yd³) GP STE PT SEG


L180H: 4.6 m³ (6.0 yd³) GP STE PT SEG

L220H: 5.2 m³ (6.8 yd³) GP STE PT SEG













Tires L150H, L180H: 775/65 R29 L3 | Tires L220H: 875/65 R29 L4

			L150H		L180H		L220H	
A	m ²	yd ²	3.1	3.7	3.5	4.2	4	4.8
B	mm	in	3,660	144.1	3,870	152.4	3,920	154.3
C	mm	in	2,110	83.1	2,150	84.6	2,270	89.4
D	mm	in	2,960	116.5	3,150	124.0	3,160	124.4
E	mm	in	1,650	65.0	1,720	67.7	1,780	70.1
F	mm	in	1,630	64.2	1,700	66.9	1,640	64.6
G	mm	in	2,930	115.4	3,040	119.7	3,230	127.2
H	mm	in	4,990	196.5	5,170	203.5	5,350	210.6
I	mm	in	7,270	286.2	7,610	299.6	7,730	304.3
J	mm	in	3,080	121.3	3,370	132.7	3,620	142.5
K	mm	in	3,340	131.5	3,710	146.1	3,940	155.1
L	mm	in	2,290	90.2	2,410	94.9	2,630	103.5
M	mm	in	9,680	381.1	9,980	392.9	10,380	408.7



Volvo L150H Specifications

L150H

Tires 26.5 R25 L3		REHANDLING								GENERAL PURPOSE						ROCK***		LIGHT MATERIAL		LONG BOOM*	
		WLA86748	WLA86749	WLA86752	WLA86754	WLA87103	WLA87106	WLA87108	WLA93724	WLA92032	WLA86749										
																					
		4.0 m³ (5.2 yd³) STE P BOE	4.4 m³ (5.8 yd³) STE P BOE	4.8 m³ (6.3 yd³) STE P BOE	5.2 m³ (6.8 yd³) STE P BOE	4.0 m³ (5.2 yd³) STE P T SEG	4.4 m³ (5.8 yd³) STE P T SEG	4.5 m³ (5.9 yd³) STE P T SEG	3.5 m³ (4.6 yd³) SPN P T SEG	6.8 m³ (8.9 yd³) LM P	4.0 m³ (5.2 yd³) STE P T SEG										
Volume, heaped ISO/SAE	m³ yd³	4.0 5.2	4.4 5.8	4.8 6.3	5.2 6.8	4.0 5.2	4.4 5.8	4.5 5.9	3.5 4.6	6.8 8.9	4.0 5.2										
Volume at 110% fill factor	m³ yd³	4.4 5.8	4.8 6.3	5.3 6.9	5.7 7.5	4.4 5.8	4.8 6.3	5.0 6.5	3.9 5	7.5 9.8	4.4 5.8										
Static tipping load, straight	kg lb	20,500 45,200	20,230 44,610	19,950 43,990	19,800 43,660	18,100 39,900	17,690 39,010	17,670 38,960	18,730 41,290	16,360 36,080	-3,550 -7,826										
at 35° turn	kg lb	18,320 40,390	18,050 39,810	17,780 39,200	17,630 38,880	16,190 35,700	15,780 34,800	15,760 34,760	16,730 36,890	14,520 32,010	-3,270 -7,209										
at full turn	kg lb	18,070 39,840	17,810 39,260	17,530 38,660	17,380 38,330	15,970 35,220	15,560 34,320	15,550 34,280	16,500 36,390	14,310 31,550	-3,230 -7,121										
Breakout force	kN lbf	201.3 45,250	191.7 43,090	183.2 41,190	182.7 41,070	202 45,340	192 43,220	184 41,460	188.0 42,270	140.0 31,480	+9 +2,023										
A	mm ft in	8,600 28'2"	8,680 28'6"	8,750 28'8"	8,750 28'9"	8,790 28'10"	8,860 29'1"	8,930 29'3"	8,850 29'0"	9,230 30'3"	+520 +1'8"										
E	mm ft in	1,230 4'1"	1,300 4'3"	1,360 4'6"	1,370 4'6"	1,400 4'7"	1,460 4'9"	1,520 5'0"	1,450 4'9"	1,790 5'10"	+10 -0,4"										
H**)	mm ft in	3,020 9'11"	2,970 9'9"	2,920 9'7"	2,920 9'7"	2,890 9'6"	2,850 9'4"	2,800 9'2"	2,870 9'5"	2,620 8'7"	+570 +1'10"										
L	mm ft in	5,720 18'9"	5,770 18'11"	5,880 19'3"	5,870 19'3"	5,880 19'3"	5,990 19'8"	6,040 19'10"	5,970 19'7"	6,140 20'2"	+570 +1'10"										
M**)	mm ft in	1,220 4'0"	1,270 4'2"	1,320 4'4"	1,320 4'4"	1,360 4'5"	1,410 4'7"	1,450 4'9"	1,420 4'8"	1,700 5'7"	-20 -0,8"										
N**)	mm ft in	1,800 5'11"	1,830 6'0"	1,860 6'1"	1,860 6'1"	1,880 6'2"	1,910 6'3"	1,930 6'4"	1,930 6'4"	1,960 6'5"	+450 +1'6"										
V	mm in	3,200 125"	3,200 125"	3,200 125"	3,400 133"	3,230 127"	3,200 125"	3,000 118"	3,230 127"	3,200 125"	0 0										
a ₁ clearance circle	mm ft in	14,640 48'0"	14,670 48'2"	14,700 48'3"	14,890 48'10"	14,750 48'5"	14,760 48'5"	14,600 47'11"	14,800 48'7"	14,940 49'0"	+340 +1'1"										
Operating weight	kg lb	25,090 55,320	25,300 55,780	25,500 56,220	25,620 56,490	24,090 53,130	24,450 53,920	24,420 53,840	25,320 55,820	24,920 54,950	+410 +904										






*) Measured with 4.0 m³ (5.2 yd³) GP bucket Note: This only applies to genuine Volvo attachments.

**) Measured to the tip of the bucket teeth or bolt-on edge. Dump height to bucket edge measured at 45° dump angle. (Spade nose buckets at 42°.)


**) Measured with L5 tires

Bucket Selection Chart

The chosen bucket is determined by the density of the material and the expected bucket fill factor. The actual bucket volume is often larger than the rated capacity, due to the features of the TP linkage, including an open bucket design, good rollback angles in all positions and good bucket filling performance. The example represents a standard boom configuration. Example: Sand and gravel. Fill factor ~ 105%. Density 1.6 t/m³. Result: The 4.0 m³ bucket carries 4.2 m³. For optimum stability always consult the bucket selection chart.

Material	Bucket fill, %		Material density		ISO/SAE bucket volume		Actual volume	
			t/m³	lb/yd³	m³	yd³	m³	yd³
Earth/Clay	~ 110		~ 1.6 ~ 1.5	~ 2,698 ~ 2,530	4.0 4.4	5.2 5.8	~ 4.4 ~ 4.8	~ 5.8 ~ 6.3
Sand/Gravel	~ 105		~ 1.6 ~ 1.5	~ 2,698 ~ 2,530	4.0 4.4	5.2 5.8	~ 4.2 ~ 4.6	~ 5.5 ~ 6.0
Aggregate	~ 100		~ 1.8 ~ 1.7 ~ 1.5	~ 3,035 ~ 2,867 ~ 2,530	4.4 4.8 5.2	5.8 6.3 6.8	~ 4.4 ~ 4.8 ~ 5.2	~ 5.8 ~ 6.3 ~ 6.8
Rock	≤ 100		~ 1.7	~ 2,867	3.5	4.6	~ 3.5	~ 4.6

The size of rock buckets is optimized for optimal penetration and filling capability rather than the density of the material.

Type of boom	Type of bucket	ISO/SAE Bucket volume	L150H	Material density: t/m³ (lb/yd³)							
				0.8 (1349)	1.0 (1686)	1.2 (2024)	1.4 (2361)	1.6 (2698)	1.8 (3035)	2.0 (3373)	
Standard boom	Rehandling*	4.4 m³ (5.8 yd³)						4.6 (6.0)		4.4 (5.8)	
		4.8 m³ (6.3 yd³)						5.0 (6.5)		4.8 (6.3)	
		5.2 m³ (6.8 yd³)						5.5 (7.2)		5.2 (6.8)	
	General purpose	4.0 m³ (5.2 yd³)						4.4 (5.8)		4.0 (5.2)	
Long boom	Rehandling*	4.0 m³ (5.2 yd³)						4.2 (5.5)		4.0 (5.2)	
		4.4 m³ (5.8 yd³)						4.6 (6.0)		4.4 (5.8)	
	General purpose	3.7 m³ (4.8 yd³)						4.1 (5.4)		3.7 (4.8)	
	Rock	3.5 m³ (4.6 yd³)							3.5 (4.6)	3.3 (4.3)	
Light material	Rehandling*	6.8 m³ (8.9 yd³)	6.8 (8.9)								
		4.0 m³ (5.2 yd³)						4.2 (5.5)		4.0 (5.2)	
		4.4 m³ (5.8 yd³)						4.6 (6.0)		4.4 (5.8)	
	General purpose	3.7 m³ (4.8 yd³)						4.1 (5.4)		3.7 (4.8)	
Rock	Rehandling*	3.5 m³ (4.6 yd³)							3.5 (4.6)	3.3 (4.3)	
		4.0 m³ (5.2 yd³)						4.2 (5.5)		4.0 (5.2)	
		4.4 m³ (5.8 yd³)						4.6 (6.0)		4.4 (5.8)	
	General purpose	3.7 m³ (4.8 yd³)						4.1 (5.4)		3.7 (4.8)	
Light material	Rehandling*	6.8 m³ (8.9 yd³)	6.8 (8.9)								
		4.0 m³ (5.2 yd³)						4.2 (5.5)		4.0 (5.2)	
		4.4 m³ (5.8 yd³)						4.6 (6.0)		4.4 (5.8)	
	General purpose	3.7 m³ (4.8 yd³)						4.1 (5.4)		3.7 (4.8)	
Bucket fill		110% 105% 100% 95%									
			Pin-on								

How to read bucket fill factor











* Including counterweight

Supplemental Operating Data

Tires 26.5 R25 L3			Standard boom						Long boom					
			26.5 R25 L4		26.5 R25 L5		775/65 R29 L3		26.5 R25 L4		26.5 R25 L5		775/65 R29 L3	
Width over tires	mm	in	+5	+0.2	+30	+1.2	+180	+7.1	+5	+0.2	+30	+1.2	+180	+7.1
Ground clearance	mm	in	+18	+0.7	+30	+1.2	+10	+0.4	+18	+0.7	+30	+1.2	+10	+0.4
Tipping load, full turn	kg	lb	+250	+551	+760	+1676	+590	+1,300	+220	+485	+640	+1,411	+500	+1,102
Operating weight	kg	lb	+400	+882	+1,060	+2,337	+760	+1,676	+400	+882	+1,050	+2,315	+750	+1,653

Volvo L180H Specifications

L180H

Tires 26.5 R25 L3		REHANDLING								GENERAL PURPOSE						ROCK***		LIGHT MATERIAL		LONG BOOM*	
		WLA86752	WLA86754	WLA86755	WLA86756	WLA867106	WLA87113	WLA87118	WLA85411	WLA91117	WLA86754										
																					
		4.8 m ³ (6.3 yd ³) STE P BOE	5.2 m ³ (6.8 yd ³) STE P BOE	5.5 m ³ (7.2 yd ³) STE P BOE	5.8 m ³ (7.6 yd ³) STE P BOE	4.4 m ³ (5.8 yd ³) STE P T SEG	4.6 m ³ (6.0 yd ³) STE P T SEG	4.8 m ³ (6.3 yd ³) STE P T SEG	4.2 m ³ (5.5 yd ³) SPN P T SEG	7.8 m ³ (10.2 yd ³) LM P	4.6 m ³ (6.0 yd ³) STE P T SEG										
Volume, heaped ISO/SAE	m ³ yd ³	4.8 6.3	5.2 6.8	5.5 7.2	5.8 7.6	4.4 5.8	4.6 6	4.8 6.3	4.2 5.5	7.8 10.2	4.6 6.0										
Volume at 110% fill factor	m ³ yd ³	5.3 6.9	5.7 7.5	6.1 7.9	6.4 8.3	4.8 6.3	5.1 6.6	5.3 6.9	4.6 6	8.6 11.2	5.1 6.7										
Static tipping load, straight	kg lb	23,670 52,190	23,520 51,860	23,350 51,480	23,210 51,180	21,540 47,500	21,560 47,540	21,360 47,090	22,250 49,060	20,430 45,040	-3,820 -8,420										
at 35° turn	kg lb	21,010 46,330	20,860 46,000	20,700 45,630	20,570 45,350	19,140 42,200	19,150 42,230	18,960 41,810	19,750 43,560	18,070 39,850	-3,480 -7,680										
at full turn	kg lb	20,710 45,660	20,560 45,330	20,390 44,970	20,260 44,680	18,860 41,600	18,880 41,620	18,690 41,200	19,470 42,930	17,800 39,260	-3,450 -7,590										
Breakout force	kN lbf	224.9 50,570	224.2 50,420	216.2 48,600	210.0 47,230	235.9 53,050	236.0 53,060	226.4 50,910	212.6 47,790	173.5 39,000	+3.9 +870										
A	mm ft in	8,890 29'2"	8,890 29'2"	8,960 29'5"	9,010 29'7"	9,000 29'6"	9,000 29'6"	9,070 29'9"	9,140 30'0"	9,360 30'8"	+470 +1'6"										
E	mm ft in	1,430 4'8"	1,430 4'8"	1,490 4'11"	1,540 5'1"	1,530 5'0"	1,530 5'0"	1,590 5'3"	1,650 5'5"	1,860 6'1"	+20 +0,6"										
H**)	mm ft in	3,060 10'0"	3,050 10'0"	3,010 9'11"	2,970 9'9"	2,990 9'10"	2,990 9'10"	2,940 9'8"	2,910 9'7"	2,690 8'10"	+500 +1'7"										
L	mm ft in	6,010 19'9"	6,010 19'9"	6,040 19'10"	6,110 20'0"	6,130 20'1"	6,170 20'3"	6,180 20'3"	6,320 20'9"	6,300 20'8"	+500 +1'7"										
M**)	mm ft in	1,330 4'4"	1,330 4'4"	1,370 4'6"	1,410 4'8"	1,420 4'8"	1,420 4'8"	1,460 4'10"	1,520 5'0"	1,610 5'3"	+20 +0,6"										
N**)	mm ft in	1,960 6'5"	1,960 6'5"	1,990 6'6"	2,000 6'7"	2,020 6'7"	2,020 6'7"	2,040 6'8"	2,080 6'10"	2,050 6'9"	+410 +1'4"										
V	mm in	3,200 125"	3,400 133"	3,400 133"	3,400 133"	3,200 125"	3,200 125"	3,200 125"	3,230 127"	3,400 133"	0 0										
a1 clearance circle	mm ft in	14,800 48'7"	14,990 49'2"	15,010 49'3"	15,040 49'4"	14,850 48'9"	14,850 48'9"	14,880 48'10"	14,960 49'1"	15,220 49'11"	+350 +1'2"										
Operating weight	kg lb	28,070 61,890	28,190 62,160	28,290 62,380	28,360 62,540	27,020 59,590	27,060 59,670	27,120 59,800	28,440 62,700	27,470 60,570	+270 +590										





*) Measured with 4.6 m³ (6.0 yd³) GP bucket Note: This only applies to genuine Volvo attachments.

**) Measured to the tip of the bucket teeth or bolt-on edge. Dump height to bucket edge measured at 45° dump angle. (Spade nose buckets at 42°.)

**) Measured with L5 tires

Bucket Selection Chart

The chosen bucket is determined by the density of the material and the expected bucket fill factor. The actual bucket volume is often larger than the rated capacity, due to the features of the TP linkage, including an open bucket design, good rollback angles in all positions and good bucket filling performance. The example represents a standard boom configuration. Example: Sand and gravel. Fill factor ~ 105%. Density 1.6 t/m³. Result: The 4.6 m³ bucket carries 4.8 m³. For optimum stability always consult the bucket selection chart

Material	Bucket fill, %		Material density		ISO/SAE bucket volume		Actual volume	
			t/m ³	lb/yd ³	m ³	yd ³	m ³	yd ³
Earth/Clay	~ 110		~ 1.7	~ 2,867	4.9	6.4	~ 4.8	~ 6.3
			~ 1.6	~ 2,698	5.2	6.8	~ 5.1	~ 6.7
			~ 1.5	~ 2,530	5.4	7.1	~ 5.3	~ 6.9
Sand/Gravel	~ 105		~ 1.7	~ 2,867	4.4	5.8	~ 4.6	~ 6.0
			~ 1.6	~ 2,698	4.6	6.0	~ 4.8	~ 6.3
			~ 1.5	~ 2,530	4.8	6.3	~ 5.1	~ 6.7
Aggregate	~ 100		~ 1.8	~ 3,035	5.2	6.8	~ 5.2	~ 6.8
			~ 1.7	~ 2,867	5.5	7.2	~ 5.5	~ 7.2
			~ 1.6	~ 2,698	5.8	7.6	~ 5.8	~ 7.6
Rock	≤ 100		~ 1.7	~ 2,867	4.3	5.6	~ 4.3	~ 5.6

The size of rock buckets is optimized for optimal penetration and filling capability rather than the density of the material.










Type of boom	Type of bucket	ISO/SAE Bucket volume	L180H Material density: t/m ³ (lb/ycd ³)							
		0.8 (1349)	1.0 (1666)	1.2 (2024)	1.4 (2361)	1.6 (2698)	1.8 (3035)	2.0 (3373)		
Standard boom	Rehandling*	5.2 m ³ (6.8 ycd ³)				5.5 (7.2)	5.2 (6.8)			
		5.5 m ³ (7.2 ycd ³)				5.8 (7.6)	5.5 (7.2)			
		5.8 m ³ (7.6 ycd ³)			6.1 (8.0)	5.8 (7.6)				
	General purpose	4.4 m ³ (5.8 ycd ³)				4.8 (6.3)	4.4 (5.8)			
		4.6 m ³ (6.0 ycd ³)				5.1 (6.7)	4.6 (6.0)			
		4.8 m ³ (6.3 ycd ³)				5.3 (6.9)	4.8 (6.3)			
	Rock	4.2 m ³ (5.5 ycd ³)					4.2 (5.5)	4.0 (5.2)		
	Light material	7.8 m ³ (10.0 ycd ³)	7.8 (10.0)							
Long boom	Rehandling*	4.8 m ³ (6.3 ycd ³)				5.0 (6.5)	4.8 (6.3)			
		5.2 m ³ (6.8 ycd ³)				5.5 (7.2)	5.2 (6.8)			
	General purpose	4.4 m ³ (5.8 ycd ³)				4.8 (6.3)	4.4 (5.8)			
		4.6 m ³ (6.0 ycd ³)					5.1 (6.7)	4.6 (6.0)		
	Rock	4.2 m ³ (5.5 ycd ³)					4.2 (5.5)	4.0 (5.2)		
	Light material	7.8 m ³ (10.0 ycd ³)	7.8 (10.0)							
Bucket fill										
110% 105% 100% 95%										
			Pin-on							

Supplemental Operating Data

				Standard boom					Long boom					
Tires 26.5 R25 L3				26.5 R25 L4	26.5 R25 L5	775/65 R29 L3			26.5 R25 L4	26.5 R25 L5	775/65 R29 L3			
Width over tires	mm	in		+5	+0.2	+30	+1.2	+130	+5	+0.2	+30	+1.2	+130	+5.1
Ground clearance	mm	in		+18	+0.7	+40	+1.6	+10	+18	+0.7	+40	+1.6	+10	+0.4
Tipping load, full turn	kg	lb		+280	+617	+770	+30.3	+600	+250	+551	+760	+29.9	+530	+20.9
Operating weight	kg	lb		+400	+882	+1,050	+2315	+920	+400	+882	+1,050	+2315	+1,120	+44.1

Volvo L220H Specifications

L220H

Tires 29.5 R25 L3			REHANDLING						GENERAL PURPOSE				ROCK***				LIGHT MATERIAL		LONG BOOM*	
			WLA86759		WLA86760		WLA86761		WLA87132		WLA87135		WLA87524		WLA85417		WLA93450		WLA86760	
																				
			5.6 m³ (7.3 yd³) STE P BOE		5.9 m³ (7.7 yd³) STE P BOE		6.3 m³ (8.2 yd³) STE P BOE		5.2 m³ (6.8 yd³) STE P T SEG		5.6 m³ (7.3 yd³) STE P T SEG		4.5 m³ (5.9 yd³) SPN P T SEG		5.0 m³ (6.5 yd³) SPN P T SEG		8.2 m³ (10.7 yd³) LM P		5.2 m³ (6.8 yd³) STE P T SEG	
Volume, heaped ISO/SAE	m³	yd³	5.6	7.3	5.9	7.7	6.3	8.2	5.2	6.8	5.6	7.3	4.5	5.9	5.0	6.5	8.2	10.7	5.2	6.8
Volume at 110% fill factor	m³	yd³	6.2	8.1	6.5	8.5	6.9	9.1	5.7	7.5	6.2	8.1	5.0	6.5	5.5	7.2	9.0	11.8	5.7	7.5
Static tipping load, straight	kg	lb	25,270	55,710	25,140	55,430	24,960	55,030	23,900	52,700	23,600	52,030	24,900	54,900	23,770	52,410	22,820	50,310	-2,890	-6370
at 35° turn	kg	lb	22,420	49,430	22,290	49,160	22,120	48,770	21,220	46,790	20,940	46,160	22,150	48,840	21,090	46,500	20,190	44,510	-2,650	-5840
at full turn	kg	lb	22,090	48,720	21,970	48,440	21,800	48,060	20,910	46,110	20,630	45,500	21,840	48,150	20,780	45,830	19,890	43,850	-2,620	-5780
Breakout force	kN	lbf	228.9	51,460	223.1	50,150	215.0	48,330	244.5	54,990	229.0	51,490	211.5	47,560	196.5	44,190	190.8	42,900	+3.4	+670
A	mm	ft in	9,270	30'5"	9,310	30'7"	9,380	30'9"	9,350	30'8"	9,460	31'0"	9,580	31'5"	9,730	31'11"	9,580	31'5"	+310	+1'
E	mm	ft in	1,470	4'10"	1,510	4'11"	1,570	5'2"	1,540	5'1"	1,640	5'5"	1,730	5'8"	1,860	6'1"	1,750	5'9"	-30	-0,6"
H**)	mm	ft in	3,160	10'4"	3,130	10'3"	3,080	10'1"	3,110	10'3"	3,040	9'11"	3,030	9'11"	2,930	9'7"	2,910	9'7"	+370	+1'2"
L	mm	ft in	6,260	20'6"	6,290	20'7"	6,370	20'11"	6,440	21'2"	6,440	21'1"	6,450	21'2"	6,510	21'4"	6,450	21'2"	+360	+1'2"
M**)	mm	ft in	1,400	4'7"	1,440	4'9"	1,480	4'10"	1,470	4'10"	1,560	5'1"	1,700	5'7"	1,800	5'11"	1,610	5'3"	-30	-0,6"
N**)	mm	ft in	2,100	6'11"	2,120	7'0"	2,150	7'1"	2,160	7'1"	2,200	7'3"	2,250	7'5"	2,300	7'6"	2,180	7'2"	+270	+10'
V	mm	in	3,400	133"	3,400	133"	3,400	133"	3,400	133"	3,400	133"	3,430	135"	3,430	135"	3,700	145"	0	0
a1 clearance circle	mm	ft in	15,570	51'1"	15,590	51'2"	15,620	51'3"	15,610	51'3"	15,670	51'5"	15,770	51'9"	15,850	52'0"	16,020	52'7"	+260	+0'10"
Operating weight	kg	lb	31,950	70,440	32,020	70,610	32,130	70,850	31,190	68,770	31,260	68,920	32,710	72,130	33,130	73,050	31,660	69,800	+380	+860

*) Measured with 5.2 m³ (6.8 yd³) bucket Note: This only applies to genuine Volvo attachments.

**) Measured to the tip of the bucket teeth or bolt-on edge. Dump height to bucket edge measured at 45° dump angle. (Spade nose buckets at 42°.)

***) Measured with L5 tires

Bucket Selection Chart

The chosen bucket is determined by the density of the material and the expected bucket fill factor. The actual bucket volume is often larger than the rated capacity, due to the features of the TP linkage, including an open bucket design, good rollback angles in all positions and good bucket filling performance. The example represents a standard boom configuration. Example: Sand and gravel. Fill factor ~ 105%. Density 1.6 t/m³. Result: The 5.2 m³ bucket carries 5.5 m³. For optimum stability always consult the bucket selection chart.

Material	Bucket fill, %		Material density		ISO/SAE bucket volume		Actual volume	
			t/m ³	lb/yd ³	m ³	yd ³	m ³	yd ³
Earth/Clay	~ 110		~ 1.6	~ 2,698	4.9	6.4	~ 5.4	~ 7.1
			~ 1.5	~ 2,530	5.2	6.8	~ 5.7	~ 7.5
			~ 1.4	~ 2,361	5.4	7.1	~ 5.9	~ 7.7
Sand/Gravel	~ 105		~ 1.7	~ 2,867	4.9	6.4	~ 5.1	~ 6.7
			~ 1.6	~ 2,698	5.2	6.8	~ 5.5	~ 7.2
			~ 1.5	~ 2,530	5.4	7.1	~ 5.7	~ 7.5
Aggregate	~ 100		~ 1.8	~ 3,035	5.6	7.3	~ 5.6	~ 7.3
			~ 1.7	~ 2,867	5.9	7.7	~ 5.9	~ 7.7
			~ 1.6	~ 2,698	6.3	8.2	~ 6.3	~ 8.2
Rock	≤100		~ 1.7	~ 2,867	4.5	5.9	~ 4.5	~ 5.9

The size of rock buckets is optimized for optimal penetration and filling capability rather than the density of the material.

Type of boom	Type of bucket	ISO/SAE Bucket volume	L220H							Material density: t/m ³ (lb/yd ³)								
			0.8 (1349)	1.0 (1686)	1.2 (2024)	1.4 (2361)	1.6 (2698)	1.8 (3035)	2.0 (3373)									
Standard boom	Rehandling*	5.6 m ³ (7.3 yd ³)						5,9 (7.7)					5,6 (7.3)					
		5,9 m ³ (7.7 yd ³)						6,2 (8.1)					5,9 (7.7)					
		6,3 m ³ (8.2 yd ³)					6,6 (8.6)		6,3 (8.2)									
	General purpose	4,9 m ³ (6.4 yd ³)							5,4 (7.1)					4,9 (6.4)				
		5,2 m ³ (6.8 yd ³)							5,7 (7.5)					5,2 (6.8)				
		5,6 m ³ (7.3 yd ³)					6,2 (8.1)		5,6 (7.3)									
Rock	4,5 m ³ (5.9 yd ³)												4,5 (5.9)				4,3 (5.6)	
	5,0 m ³ (6.5 yd ³)							5,0 (6.5)					5,3 (6.9)					
	Light material	8,2 m ³ (10.7 yd ³)	8,2 (10.7)															
Long boom	Rehandling*	5,6 m ³ (7.3 yd ³)						5,9 (7.7)					5,6 (7.3)					
		5,9 m ³ (7.7 yd ³)						6,2 (8.1)		5,9 (7.7)								
	General purpose	4,9 m ³ (6.4 yd ³)							5,4 (7.1)					4,9 (6.4)				
Rock	4,5 m ³ (5.9 yd ³)											4,5 (5.9)				4,3 (5.9)		
	Light material	8,2 m ³ (10.7 yd ³)	8,2 (10.7)															
Bucket fill 110% 105% 100% 95%																		
How to read bucket fill factor																		
* Including counterweight																		

How to read bucket fill factor

* Including counterweight

Supplemental Operating Data

			Standard boom						Long boom					
Tires 29.5 R25 L4			29.5 R25 L3		29.5 R25 L5		875/65 R29 L4		29.5 R25 L3		29.5 R25 L5		875/65 R29 L4	
Width over tires	mm	in	-20	-0.8	+35	+1.4	+95	+3.7	-20	-0.8	+35	+1.4	+95	+3.7
Ground clearance	mm	in	±0	±0	+40	+1.6	-10	-0.4	±0	±0	+40	+1.6	-20	-0.8
Tipping load, full turn	kg	lb	-100	-3.9	+1,010	+39.8	+180	+7.1	-90	-3.5	+930	+36.6	+180	+7.1
Operating weight	kg	lb	-80	-3.2	+1,490	+58.7	+650	+25.6	-80	3.2	+1,500	+59.1	+650	+25.6

Equipment

STANDARD EQUIPMENT			
	L150H	L180H	L220H
Engine			
Exhaust after-treatment system	•	•	•
Two stage air cleaner, pre-cleaner, primary and secondary filter	•	•	•
Preheating of induction air	•	•	•
Fuel pre-filter with water trap	•	•	•
Fuel filter	•	•	•
Crankcase breather oil trap	•	•	•
Exterior radiator air intake protection	•	•	•
Drivetrain			
Automatic Power Shift	•	•	•
Fully automatic gearshifting, 1-4	•	•	•
PWM-controlled gearshifting	•	•	•
Forward and reverse switch by hydraulic lever console	•	•	•
Rimpull control	•	•	•
Indicator glass for transmission oil level	•	•	•
Differentials: Front, 100% hydraulic diff lock. Rear, conventional.	•	•	•
Optishift with Lock-up, RBB	•	•	•
Lock-up first gear	•	•	•
Electrical system			
24 V, pre-wired for optional accessories	•	•	•
Alternator 24V/80A/2280W	•	•	•
Battery disconnect switch	•	•	•
Fuel gauge	•	•	•
Hour meter	•	•	•
Electric horn	•	•	•
Instrument cluster:			
Fuel level			
Diesel Exhaust Fluid/AdBlue level	•	•	•
Transmission temperature			
Coolant temperature			
Instrument lighting			
Lighting:			
Twin halogen front headlights with high and low beams			
Parking lights	•	•	•
Double brake and tail lights			
Turn signals with flashing hazard light function			
Halogen work lights (2 front and 2 rear)			

STANDARD EQUIPMENT			
	L150H	L180H	L220H
Contronic monitoring system			
Monitoring and logging of machine data	•	•	•
Contronic display	•	•	•
Fuel consumption	•	•	•
Diesel Exhaust Fluid/AdBlue consumption	•	•	•
Ambient temperature	•	•	•
Clock	•	•	•
Test function for warning and indicator lights	•	•	•
Brake test	•	•	•
Test function, sound level at max fan speed	•	•	•
Warning and indicator lights:			
Battery charging	•	•	•
Parking brake			
Warning and display message:			
Regeneration			
Engine coolant temperature			
Charge-air temperature			
Engine oil temperature			
Engine oil pressure			
Transmission oil temperature			
Transmission oil pressure			
Hydraulic oil temperature	•	•	•
Brake pressure			
Parking brake applied			
Brake charging			
Overspeed at direction change			
Axle oil temperature			
Steering pressure			
Crankcase pressure			
Attachment lock open			
Safety Belt Warning			
Level warnings:			
Fuel level			
Diesel Exhaust Fluid/AdBlue level			
Engine oil level			
Engine coolant level	•	•	•
Transmission oil level			
Hydraulic oil level			
Washer fluid level			
Engine torque reduction in case of malfunction indication:			
High engine coolant temperature	•	•	•
High engine oil temperature			
Low engine oil pressure			
High crankcase pressure			
High charge-air temperature			
Engine shutdown to idle in case of malfunction indication:			
High transmission oil temperature	•	•	•
Slip in transmission clutches			
Keypad, background lit	•	•	•
Start interlock when gear is engaged	•	•	•

Equipment

STANDARD EQUIPMENT			
	L150H	L180H	L220H
Hydraulic system			
Main valve, double acting 2-spool with hydraulic pilots	•	•	•
Variable displacement axial piston pumps (3) for:			
1 Working hydraulics, Pilot hydraulics and Brake system	•	•	•
2 Working hydraulics, Pilot hydraulics, Steering and Brake system			
3 Cooling fan and Brake system			
Electro-hydraulic servo controls	•	•	•
Electronic hydraulic lever lock	•	•	•
Automatic boom kick-out	•	•	•
Automatic bucket positioner	•	•	•
Double-acting hydraulic cylinders	•	•	•
Indicator glass for hydraulic oil level	•	•	•
Hydraulic oil cooler	•	•	•
Brake system			
Dual brake circuits	•	•	•
Dual brake pedals	•	•	•
Secondary brake system	•	•	•
Parking brake, electro-hydraulic	•	•	•
Brake wear indicators	•	•	•
Cab			
ROPS (ISO 3471), FOPS (ISO 3449)	•	•	•
Single key kit door/start	•	•	•
Acoustic inner lining	•	•	•
Cigarette lighter, 24 V power outlet	•	•	•
Lockable door	•	•	•
Cab heating with fresh air inlet and defroster	•	•	•
Fresh air inlet with two filters	•	•	•
Automatic heat control	•	•	•
Floor mat	•	•	•
Dual interior lights	•	•	•
Interior rear-view mirrors	•	•	•
Dual exterior rear-view mirrors	•	•	•
Sliding window, right side	•	•	•
Tinted windshield glass	•	•	•
Retractable seatbelt (SAE J386)	•	•	•
Adjustable steering wheel	•	•	•
Storage compartment	•	•	•
Document pocket	•	•	•
Sun visor	•	•	•
Beverage holder	•	•	•
Windshield washer front and rear	•	•	•
Windshield wipers front and rear	•	•	•
Interval function for front and rear wipers	•	•	•

STANDARD EQUIPMENT			
	L150H	L180H	L220H
Service and maintenance			
Engine oil remote drain and fill	•	•	•
Transmission oil remote drain and fill	•	•	•
Lubrication manifolds, ground accessible	•	•	•
Pressure check connections: transmission and hydraulic, quick-connects	•	•	•
Quick-fit hydraulic oil fill	•	•	•
Tool box, lockable	•	•	•
External equipment			
Orange hand rails	•	•	•
Fenders, front and rear	•	•	•
Viscous cab mounts	•	•	•
Rubber engine and transmission mounts	•	•	•
Frame, joint lock	•	•	•
Vandalism lock prepared for			
Engine compartment	•	•	•
Radiator grille			
Lifting eyes	•	•	•
Tie-down eyes	•	•	•
Fabricated counterweight	•	•	•
Counterweight, pre-drilled for optional guards	•	•	•

OPTIONAL EQUIPMENT			
	L150H	L180H	L220H
Engine			
Air pre-cleaner, cyclone type	•	•	•
Air pre-cleaner, oil-bath type	•	•	•
Air pre-cleaner, turbo type	•	•	•
Engine auto shutdown	•	•	•
Engine delayed shutdown	•	•	•
Engine block heater 230V/110V	•	•	•
Fuel fill strainer	•	•	•
Fuel heater	•	•	•
Hand throttle control	•	•	•
Max. fan speed, hot climate	•	•	•
Radiator, corrosion-protected	•	•	•
Reversible cooling fan	•	•	•
Reversible cooling fan and axle oil cooler	•	•	•
Tires			
26.5 R25	•	•	—
775/65 R29	•	•	—
29.5 R25	—	—	•
875/65 R29	—	—	•
Drivetrain			
Diff lock front 100%, Limited Slip rear	•	•	•
Speed limiter	•	•	•
Wheel/axle seal guards	•	•	•
Electrical system			
Anti-theft device	•	•	•
Emergency stop	•	•	•
Locking device, Tag out Lock out	•	•	•
Headlights, assym. left	•	•	•
License plate holder, lighting	•	•	•
Rear vision system, colour LCD monitor in the cab	•	•	•
Rear view mirrors, Long arm	•	•	•
Rear view mirrors, adjustable, el.heated, Long arm	•	•	•
Reduced function working lights, reverse gear activated	•	•	•
Reverse alarm, audible	•	•	•
Reverse alarm, white noise	•	•	•
Reverse warning light, strobe lighting	•	•	•
Seatbelt indicator, external	•	•	•
Shortened headlight support brackets	•	•	•
Side marker lamps	•	•	—
Warning beacon LED	•	•	•
Warning beacon LED automatic	•	•	•
LED Head Light	•	•	•
LED tail light	•	•	•
LED working lights, attachments	•	•	•
LED working lights on cab, front and rear	•	•	•
LED working lights on cab, front, 2 alt. 4 LED lamps	•	•	•
LED working lights on cab, rear, 2 alt. 4 LED lamps	•	•	•
LED working lights, rear in grille, 2 LED lamps	•	•	•
LED working lights, front above head lamps, 2 LED lamps	•	•	•
LED work lights, side on cab, 4 LED lamps	•	•	•
LED light packages	•	•	•
Working lights halogen, attachments	•	•	•
Working lights on cab halogen, front and rear	•	•	•
Working lights on cab halogen, rear	•	•	•
Electrical distribution unit 24 volt	•	•	•
Alternator 120 amp, heavy-duty	•	•	•
Radar detect system	•	•	•
Forward camera, colour	•	•	•
Parking brake alarm, audible for air susp seats	•	•	•
Jump start connector, NATO-Type	•	•	•
Max Boom height	•	•	•
Can Bus Interface	•	•	•
Delayed Engine Shutdown	•	•	•
Co Pilot available	•	•	•
Rearview camera in Co pilot	•	•	•
OnBoard Weighing	•	•	•
Tire pressure monitoring	•	•	•
MAP	•	•	•

OPTIONAL EQUIPMENT			
	L150H	L180H	L220H
Hydraulic system			
Boom suspension system	•	•	•
Separate attachment locking	•	•	•
Arctic kit, for 3rd function	•	•	•
Boom cylinder hose and tube guards	•	•	•
Hydraulic fluid, biodegradable, Volvo	•	•	•
Hydraulic fluid, fire-resistant	•	•	•
Hydraulic fluid, for hot climate	•	•	•
Hydraulic 3rd function	•	•	•
Hydraulic 3rd-4th function	•	•	•
Single lever control, hydraulics 2 functions	•	•	•
Single lever control, hydraulics 3 functions	•	•	•
Single lever control, hydraulics 4 functions	•	•	•
Brake system			
Oil cooler and filter front & rear axle	•	•	•
Stainless steel, brake lines	•	•	—
Cab			
Anchorage for Operator's manual	•	•	•
Automatic Climate Control, ACC	•	•	•
ACC control panel, with Fahrenheit scale	•	•	•
Asbestos dust protection filter	•	•	•
Ashtray	•	•	•
Cab air pre-cleaner, cyclone type	•	•	•
Carbon filter	•	•	•
Cover plate, under cab	•	•	•
Lunch box holder	•	•	•
Volvo Armrest, operator's seat, left	•	•	•
Operator's seat, Volvo air susp, heavy-duty, high back, heated	•	•	•
Operator's seat, (air seat std) 2-point seat belt	•	•	•
Operator's seat, (air seat std) 3-point seat belt	•	•	•
Operator's seat, Premium Comfort ISRI	•	•	•
Operator's seat, Premium Comfort ISRI 3-point seat belt	•	•	•
Radio installation kit incl. 12 volt outlet, left side	•	•	•
Radio installation kit incl. 12 volt outlet, right side	•	•	•
Radio (with AUX, Bluetooth and USB connection)	•	•	•
DAB Radio	•	•	•
Subwoofer	•	•	•
Steering wheel knob	•	•	•
Sun blinds, rear windows	•	•	•
Sun blinds, side windows	•	•	•
Timer cab heating	•	•	•
Window, sliding, door	•	•	•
Universal door/ignition key	•	•	•
Remote door opener	•	•	•
Forward view mirror	•	•	•
Cab heater power outlet 240V	•	•	•
Cab, Hot applications. Roof, steel	•	•	•
Fire extinguisher cab	•	•	•
Outside steel protection cab	•	•	•
Rear view mirrors long arm, cab	•	•	•
Reinforced windshield, flat	•	•	•

Equipment

OPTIONAL EQUIPMENT			
	L150H	L180H	L220H
Service and maintenance			
Automatic lubrication system	•	•	•
Automatic lubrication system for long boom	•	•	•
Grease nipple guards	•	•	•
Oil sampling valve	•	•	•
Quick engine oil change	•	•	•
Refill pump for grease to lube system	•	•	•
Tool kit	•	•	•
Wheel nut wrench kit	•	•	•
CareTrack, GSM, GSM/Satellite	•	•	•
Telematics, Subscription	•	•	•
Belly guard front	•	•	•
Belly guard rear	•	•	•
Cover plate, heavy-duty, front frame	•	•	•
Cover plate, rear frame	•	•	•
Cab roof, heavy-duty	•	•	•
Guards for front headlights	•	•	•
Guards for radiator grill	•	•	•
Guards for tail lights	•	•	•
Windows, side and rear guards	•	•	•
Windshield guard	•	•	•
Corrosion protection, painting of machine	•	•	•
Corrosion protection, painting of attachment bracket	•	•	—
Option for machines without dinitrol	•	•	•
Bucket Teeth protection	•	•	—
Other Equipment			
CE-marking	•	•	•
Comfort Drive Control (CDC)	•	•	•
Counterweight, logging	•	•	•
Counterweight, signal painted, chevrons	•	•	•
Secondary steering with automatic test function	•	•	•
Sound decal, EU	•	•	•
Sound decal, USA	•	•	•
Reflecting stickers (decals), machine contour	•	•	•
Reflecting stickers (stripes), machine contour Cab	•	•	•
Noise reduction kit, exterior	•	•	•
Sign, 50 km/h	•	—	—

OPTIONAL EQUIPMENT			
	L150H	L180H	L220H
External equipment			
Cab ladder, rubber-suspended	•	•	•
Escape Ladder, left fender	•	•	•
Handles on counterweight	•	•	•
Deleted front mudguards	•	•	•
Fire suppression system	•	•	•
Mudguards, full cover, front and rear for 80-series tires	•	•	•
Mudguards, full cover, front and rear for 65-series tires	•	•	•
Long boom	•	•	•
Tow hitch	•	•	•
Attachments			
Buckets:	•	•	•
Rock straight or spade nose	•	•	•
General purpose	•	•	•
Re-handling	•	•	•
Side-dump	•	•	•
Light material	•	•	•
Wear parts:	•	•	•
Bolt-on and weld-on bucket teeth	•	•	•
Segments	•	•	•
Cutting edge in three sections, bolt-on	•	•	•
Fork equipment	•	•	•
Material handling arm	•	•	•
Log grapples	•	•	•

SELECTION OF VOLVO OPTIONAL EQUIPMENT

Additional auxiliary hydraulics




Central lubrication system



Fire suppression system



External axle oil cooling



LED light packages



Long boom



Not all products are available in all markets. Under our policy of continuous improvement, we reserve the right to change specifications and design without prior notice. The illustrations do not necessarily show the standard version of the machine.

V O L V O